## Calibration Certificate

Issued By: Castle Group Ltd

Date Of Issue: 14/06/17

Certificate No : 000000/00000 Page 1 of 3

All instruments are tested to check compliance with particular specifications. These specifications may be appropriate British Standards, or if the instrument was not originally designed to meet any British Standard, or when the instrument was originally manufactured a relevant British Standard did not exist, the instrument will be tested to the manufacturer's original specification.

Absolute calibration of vibration calibrators and vibration meters is checked at one or more standard frequencies against an independent sound source with calibration directly traceable to the Physikalisch-Technische Bundesanstalt (PTB) in Germany. The PTB reference applicable for the calibration of the test equipment is shown below.

The performance of the instrument was determined by comparison with the manufacturers' specification as found in the instrument handbook or other technical publication. Any significant uncertainty of the measuring system will also be included.

The instrument was allowed to stabilise for a period of 30 minutes prior to measurements made.

The ambient temperature and relative humidity throughout calibration were 22 ±2 °C and 50% RH respectively.

### Instruments used to carry out this calibration are as follows: -

Vibration Calibrator: SV111 Serial Number 25039 Vibration Exciter: GA606 Serial Number 4357

Applicable Reference: PTB-17012-2017, reference no: 1.71-1508/0317.

Subject of Calibration: GA2005H

Instrument: HARM (Hand Arm Risk Measurement) Vibration Meter

Serial No: 000000

Sensitivity (mV/g)

Accelerometer Type: KD1006 Accelerometer Serial No:

X Axis:

Y Axis: Calibration Coefficient Y Axis:

X Axis:

Z Axis: Z Axis:

Basis Of Test: Compliance to Manufacturer's Original Specification

Calibrated By: Checked By: A N Engineer A N O Engineer (Approved Signatory) (Approved Signatory)

Date of Calibration: 14 Jun 2017 Recalibration Due: 01 Jul 2018

Completed Status: Pass

Client: End User Company Name

Address: Place

Street Location Town County Postcode

Client Reference: If Applicable

### Castle Group Ltd



### **CALIBRATION RESULTS**

Page 2 of 3 Pages

Date: 14/06/17 Certificate No: 000000/00000 Calibrated By: A N Engineer

## Castle

### INDICATED RESPONSE (Reference Range) Relative to 10.02ms<sup>2</sup> at 159.20Hz

**HARM** (TRANSDUCER = 10mV)

PARAMETER	ACTUAL VALUE			PREFERRED	TOLERANCE
	Х	Υ	Z	VALUE	TOLENANGE
METRIC (ms²)				1.009	0.9525 to 1.0687
dB (Ref 1e-6)				120.077	119.577 to 120.577
IMPERIAL (fts²)				3.310	3.125 to 3.506
g				0.1029	0.0971 to 0.1090

### **RANGE TEST**

HARM Weighted Response - Relative to 10.0ms<sup>2</sup> at 160Hz

LINEARITY RESPONSE The method employed was a direct electrical signal injection on the reference range.

TARGET LEVEL		TOLERANCE		
(ms <sup>-2</sup> )	Х	Y	Z	(ms <sup>-2</sup> )
1.00				0.95 - 1.05
10.00				9.50 - 10.50
100.00				95.00 - 105.00

LINEARITY RESPONSE (Other Measurement Ranges) The method employed was a direct electrical signal injection.

RANGE	TARGET LEVEL (ms <sup>2</sup> )	<b>READING</b> (X ONLY)	TOLERANCE (ms <sup>2</sup> )
0.02 - 100.0	0.10		0.095 - 0.105
0.02 - 100.0	1.00		0.95 - 1.05
0.02 - 100.0	10.00		9.50 - 10.50
0.1 - 500.0	0.10		0.095 - 0.105
0.1 - 500.0	1.00		0.95 - 1.05
0.1 - 500.0	10.00		9.50 - 10.50
1.00 - 5000.0	1.00		0.95 - 1.05
1.00 - 5000.0	10.00		9.50 - 10.50
1.00 - 5000.0	100.00		95.00 - 105.00

### **CALIBRATION RESULTS**

Page 3 of 3 Pages

Date: 14/06/17 Certificate No: 000000/00000 Calibrated By: A N Engineer

# Castle

### **FILTER TESTS**

**HARM** (Hand Arm Risk Measurement)

Wh FILTER TEST. The method employed was a direct electrical signal injection on the reference range.

FREQUENCY TARGET LEVEL		READING			TOLERANCE
(Hz)	(ms²)	Х	Y	Z	(ms <sup>-2</sup> )
2.0	9.92				0.00 - 12.06
5.0	54.14				44.51 - 65.84
16.0	89.92				82.04 - 96.38
80.0	20.09				18.54 - 21.78
160.0	10.00				9.95 - 10.05
800.0	1.85				1.71 – 2.00
1,600.0	0.53				0.44 - 0.65

### Uncertainties of the measurement

The uncertainties in the table of results correspond to an estimated confidence probability of not less than 95%.

<sup>\*</sup> Notes